N35-03

Network Application Platform

N35-03 is a medium- and high-end network security product based on the X86 architecture. The complete PC adopts a standard 2U 19" rack-mounted chassis with an internal modular design, which is convenient for expanding LAN ports and storage expansion. The N35 has 5 front ENS expansion slots (optional 7 x ENS expansion slots), supporting up to 64 x Gigabit LAN ports or 28 x 10-Gigabit LAN ports, which can meet various network security application requirements in the market. It can be widely used in the hardware requirements of various network security service applications such as load balancing, data audit, application delivery, Internet behavior management and audit, next-generation firewall, traffic management, VPN, IDS/IPS, UTM, etc.



Product Features



Supports

of processors



Multiple







hard disk

encryption,

intrusion

detection and BPI port














Multinetwork expansion slot


Support forced Bypass switch


Support VGA Optional IPMI function

Product Dimensions Drawing

multiple series memory slots







(Please refer to the user manual to check detailed specifications and dimensions) (unit: MM)

Product Specifications

| Item | | Description | |
|--|-----------|--|--|
| System Configuration | Processor | Supports Intel® 8th/9th Gen Core, Xeon E series, Celeron, Pentium and other LGA1151 packaging processors | |
| | Chipset | Intel®C246 | |
| | Memory | Provides 4 x DDR4 memory slot, supports Un-buffered ECC and Non-ECC memories, and the maximum capacity of the complete PC is 128GB; | |
| Chava an David | SATA | Supports 2 x SATA3.0 port (one of which is multiplexed with MSATA), and standard configuration of 1 x hard disk bay | |
| Storage Port | MSATA | 1 x MSATA slot | |
| I/O Do wh | USB | 2 x USB3.0 port (external); 2 x USB3.0 pin (built-in) | |
| I/O Port | СОМ | 1 x RJ45 Console port (external); 1 x RS-232 serial port pin (built-in) | |
| Display Port | | 1x VGA port | |
| Network card chip | | Intel® I210/I211 | |
| LAN port | | 6 x Gigabit electrical port + 4 x Gigabit optical port Note: N35-03-09 is equipped with 2 x Gigabit electrical port, one of which can be replaced by an IPMI port (subject to actual configuration) | |
| IPMI | | Optional BMC module, supporting IPMI (Intelligent Platform Management Interface) function | |
| Expansion | PCIE | 1 x PCIE X8 (X4 signal) | |
| Bus | ENS | 5 x ENS expansion slot (7 optional), Note: 4/6/8 ENS expansion slots are optional for N35-03-09 configuration | |
| Matched motherboard | | NET-1836VD2N series | |
| Working Environment | | Working temperature: 0°C -40°C | |
| Storage Environment | | Storage temperature: -20°C ~ 70°C; storage humidity: 10% ~ 90% (non-condensing state) | |
| Power supply | | Supports 350W redundant AC power supply (optional 250W single power supply) | |
| Overall Dimensions (excluding mounting ears) | | 440mm(W)x88mm(H)x550mm(D) | |
| Supported Operating Systems | | Linux OS (kernel version 2.6 and above). Please refer to the product manual for details | |

Ordering Information

| Part No. | Model | Description |
|-------------|---|---|
| 0010-189991 | N35-03B-06/I5- 8500/8G/1T/6ENS/250W single power supply | Standard 2U rack-mounted complete PC/I5-8500 3.0G 6C/8G memory/1T HDD/2 x Gigabit electrical port/6*ENS network card expansion slot/1*PCIE X8 slot/2*USB/1*console port/250 single power supply |
| 0010-190001 | N35-03B-07/ E-2278GE/8G/1T/5ENS/350W redundant power supply | Standard 2U rack-mounted complete PC/E-2278GE 3.3G 8C/8G memory/1T HDD/6 x Gigabit electrical port (2 groups of BP)/ 4 x Gigabit optical port/5*ENS network card expansion slot/1*PCIe X8 slot/2*USB 3.0/1*console port/350W redundant power supply |
| 0010-190011 | N35-03B-08/I7- 8700/8G/1T/7ENS/350W redundant power supply | Standard 2U rack-mounted complete PC/I7-8700 3.2G 6C/8G memory/1T HDD/6 x Gigabit electrical port (2 groups of BP) 4 x Gigabit optical port/7*ENS network card expansion slot/1*PCIE X8 slot/2*USB/1*console port/350W redundant power supply |
| 0010-190021 | N35-03B-09/I7- 8700/8G/1T/8ENS/350W redundant power supply | Standard 2U rack-mounted complete PC/I7-8700 3.2G 6C/8G memory/1T HDD/2 x Gigabit electrical port/8*ENS network card expansion slot/1*PCIE X8 slot/2*USB/1*console port/350W redundant power supply |

Note: EVOC Intelligent reserves the right to final interpretation of product specifications and ordering information etc.